

Trade name: R-454B**Current version :** 2.0.0, issued: 26.06.2024**Replaced version:** 1.0.0, issued: 14.12.2023**Region:**
GER**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifier****Trade name****R-454B****UFI:****1QM2-50SE-F004-T6SW****1.2 Relevant identified uses of the substance or mixture and uses advised against****Relevant identified uses of the substance or mixture**

Industrial Use

Professional use

Refrigerant

Uses advised against

Consumer use

1.3 Details of the supplier of the safety data sheet**Address**

TEGA - Technische Gase und Gasetechnik GmbH

Werner-von-Siemens-Straße 18

97076 Würzburg

Telephone no. +49 931 2093-220

Fax no. +49 931 2093-180

e-mail kaeltmittel@tega.de

Advice on Safety Data Sheet

sdb_info@umco.de

1.4 Emergency telephone number

For medical advice (in German and English):

+49 (0)551 192 40 (Gif tinformat ionszentrum Nord)

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture****Classification in accordance with Regulation (EC) No 1272/2008 (CLP)**

Flam. Gas 1B; H221

Press. Gas liq.; H280

Classification information

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

2.2 Label elements**Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)****Hazard pictograms**

GHS02



GHS04

Signal word

Danger

Trade name: R-454B

Current version : 2.0.0, issued: 26.06.2024

Replaced version: 1.0.0, issued: 14.12.2023

Region:
GER**Hazard statement(s)**

H221 Flammable gas.
H280 Contains gas under pressure; may explode if heated.

Precautionary statement(s)

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P377 Leaking gas fire: Do not extinguish, unless leak can be stopped safely.
P381 In case of leakage, eliminate all ignition sources.
P410+P403 Protect from sunlight. Store in a well-ventilated place.

UFI:

1QM2-50SE-F004-T6SW

Supplemental label elements

Contains fluorinated greenhouse gases (HFC-32, HFC-1234yf).

2.3 Other hazards

This product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher. Danger of suffocation by displacement of air / oxygen. Contact with the liquid can cause cold burns or frostbite. Abuse or intentional inhalation can be fatal as a result of effects on the heart without alarming symptoms.

PBT assessment

The product is not considered to be a PBT.

vPvB assessment

The product is not considered to be a vPvB.

SECTION 3: Composition/information on ingredients**3.1 Substances**

Not applicable. The product is not a substance.

3.2 Mixtures**Chemical characterization**

Fluorinated hydrocarbons

Hazardous ingredients

No	Substance name	Additional information	
	CAS / EC / Index / REACH no	Classification (EC) 1272/2008 (CLP)	Concentration %
1	difluoromethane		
	75-10-5 200-839-4 - 01-2119471312-47	Flam. Gas 1B; H221 Press. Gas liq.; H280	>= 50,00 - < 70,00 Vol%
2	2,3,3,3-tetrafluoroprop-1-ene		
	754-12-1 468-710-7 - 01-0000019665-61	Flam. Gas 1B; H221 Press. Gas liq.; H280	>= 25,00 - < 50,00 Vol%

Full Text for all H-phrases and EUH-phrases: pls. see section 16

No	Note	Specific concentration limits	M-factor (acute)	M-factor (chronic)
2	-	Flam. Gas 1A; H220: C >= 6,201% Flam. Gas 1B; H221: C >= 12,3%	-	-

SECTION 4: First aid measures**4.1 Description of first aid measures****General information**

Trade name: R-454B**Current version :** 2.0.0, issued: 26.06.2024**Replaced version:** 1.0.0, issued: 14.12.2023**Region:**
GER

In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. Remove affected person from danger area, lay him down. Seek medical advice immediately.

After inhalation

Remove affected persons from dangerous area by observing suitable respiratory protection measures. Ensure supply of fresh air. Irregular breathing/no breathing: artificial respiration. Call a doctor immediately.

After skin contact

In case of contact with skin wash off immediately with soap and water. Rinse with much water in case of frostbites. Remove clothes only after unfreezing. Cover wounds with sterile dressing. Call a doctor immediately.

After eye contact

Remove contact lenses. Rinse eye thoroughly under running water keeping eyelids wide open and protecting the unaffected eye (at least 10 to 15 minutes). Seek medical assistance.

After ingestion

Rinse the mouth thoroughly with water. Do not induce vomiting. Never give anything by mouth to an unconscious person. Call a doctor.

4.2 Most important symptoms and effects, both acute and delayed**Symptoms**

The following symptoms may occur: cardiac arrhythmia; anesthetic effect; Light-headedness; Dizziness; confusion; Unconsciousness; muscle incoordination; respiratory arrest. Contact with liquefied gas can cause damage (frostbite) due to rapid evaporative cooling.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically and supportively.

SECTION 5: Firefighting measures**5.1 Extinguishing media****Suitable extinguishing media**

Alcohol resistant foam, CO₂, powders, water spray

Unsuitable extinguishing media

High power water jet

5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon monoxide and carbon dioxide; Hydrogen fluoride (HF); Carbonyl fluoride; fluorine compounds; Exposure to heat may cause bursting of the vessels. Vapours can form a highly flammable mixture with air.

5.3 Advice for firefighters

Use self-contained breathing apparatus. Wear full protective suit. Containers close to fire should be transferred to a safe place. Cool closed containers exposed to fire with water. Pressure increase, bursting and explosion hazard during heating. Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures****For non-emergency personnel**

Refer to protective measures listed in sections 7 and 8. Provide good room ventilation even at ground level (vapours are heavier than air). Do not breathe gas. Keep away from ignition sources. Use personal protective clothing. Cordon and mark contaminated area. Remove persons to safety. Avoid skin contact with leaking liquid (danger of frostbite!).

For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

6.2 Environmental precautions

Avoid release in the environment. Suppress gases/vapours/mists with water spray jet.

6.3 Methods and material for containment and cleaning up

Ensure adequate ventilation. Dispose of absorbed material in accordance with the regulations.

Trade name: R-454B

Current version : 2.0.0, issued: 26.06.2024

Replaced version: 1.0.0, issued: 14.12.2023

Region:
GER**6.4 Reference to other sections**

Information regarding safe handling, see section 7. Information regarding personal protective measures, see section 8. Information regarding waste disposal, see section 13.

SECTION 7: Handling and storage**7.1 Precautions for safe handling****Advice on safe handling**

Only qualified and trained persons are authorised to handle. Provide good ventilation at the work area (local exhaust ventilation, if necessary). To be used only according to instructions for use. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose containers heat or sources of ignition. In case of accidental release: danger due to low temperature of the liquid product. The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Comply with the health and safety at work laws. Use explosion-proof apparatus and fittings.

General protective and hygiene measures

Wash hands before breaks and after work. Do not inhale gases. Do not eat, drink or smoke during work time. Keep away from foodstuffs and beverages. Have emergency shower available. Provide eye wash fountain in work area.

Advice on protection against fire and explosion

Isolate from sources of heat, sparks and open flame. Take precautionary measures against electrostatic loading (earthing necessary during loading operations). Electrical equipment should be protected to the appropriate standard. Vapours can form an explosive mixture with air.

7.2 Conditions for safe storage, including any incompatibilities**Technical measures and storage conditions**

Keep container tightly closed in a cool, well-ventilated place, open and handle carefully. Protect from heat and direct sunlight.

Recommended storage temperature

Value	<	52	°C
-------	---	----	----

Storage stability

Value	>	10	a
Comments	When stored properly, the storage life is unlimited.		

Requirements for storage rooms and vessels

Containers which are opened must be carefully closed and kept upright to prevent leakage. Always keep in containers of same material as the original.

Incompatible products

Do not store together with: self-heating substances and mixtures; self-reactive substances and mixtures; flammable substances; oxidizing agents; pyrophoric substances; explosives; toxic substances and mixtures; toxic substances and mixtures

Storage Class according TRGS 510

2A	Gases (except aerosol dispensers and lighters)
----	--

7.3 Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection**8.1 Control parameters****Occupational exposure limit values**

No	Substance name	CAS no.	EC no.
1	2,3,3,3-tetrafluoroprop-1-ene	754-12-1	468-710-7
	TRGS 900		
	2,3,3,3-Tetrafluorpropen		

Trade name: R-454B

Current version : 2.0.0, issued: 26.06.2024

Replaced version: 1.0.0, issued: 14.12.2023

Region:
GER

WEL long-term (8-hr TWA reference period)	950	mg/m ³	200	ml/m ³
Ceiling Limit	2 (II)			
Notes	Y			

DNEL, DMEL and PNEC values**DNEL values (worker)**

No	Substance name	CAS / EC no		
	Route of exposure	Exposure time	Effect	Value
1	difluoromethane	75-10-5 200-839-4		
	inhalative	Long term (chronic)	systemic	7035 mg/m ³
2	2,3,3,3-tetrafluoroprop-1-ene	75-12-1 468-710-7		
	inhalative	Long term (chronic)	systemic	950 mg/m ³
	inhalative	Short term (acut)	systemic	186400 mg/m ³

DNEL value (consumer)

No	Substance name	CAS / EC no		
	Route of exposure	Exposure time	Effect	Value
1	difluoromethane	75-10-5 200-839-4		
	inhalative	Long term (chronic)	systemic	750 mg/m ³
2	2,3,3,3-tetrafluoroprop-1-ene	75-12-1 468-710-7		
	inhalative	Long term (chronic)	systemic	113,1 mg/m ³
	inhalative	Short term (acut)	systemic	186400 mg/m ³

PNEC values

No	Substance name	CAS / EC no	
	ecological compartment	Type	Value
1	difluoromethane	75-10-5 200-839-4	
	water	fresh water	0,313 mg/L
	water	fresh water sediment	1,807 mg/kg dry weight
2	2,3,3,3-tetrafluoroprop-1-ene	75-12-1 468-710-7	
	water	fresh water	0,1 mg/L
	water	marine water	0,01 mg/L
	water	fresh water sediment	1,51 mg/kg dry weight
	water	marine water sediment	0,151 mg/kg dry weight
	soil	-	1,49 mg/kg dry weight

8.2 Exposure controls**Appropriate engineering controls**

Ensure adequate ventilation, local exhaust at the work station if necessary. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn. Explosion-proof general and local exhaust ventilation.

Personal protective equipment**Respiratory protection**

Self-contained breathing apparatus. In case of insufficient ventilation or long-term effect use breathing apparatus. Danger of suffocation due to high concentrations in breathing air.

Respiratory filter (gas) : AX

Eye / face protection

Trade name: R-454B

Current version : 2.0.0, issued: 26.06.2024

Replaced version: 1.0.0, issued: 14.12.2023

Region:
GER

Tightly fitting safety glasses (EN 166).

Hand protection

Low-temperature-resistant gloves (EN 511). Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Appropriate Material Leather

Other

Chemical-resistant work clothes. Fire-resistant antistatic protective clothing. Protective shoes.

Environmental exposure controls

Information regarding waste disposal, see chapter 13.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

State of aggregation	
gas	
Form	
liquified gas	
Colour	
colourless	
Odour	
slightly like ether	
pH value	
No data available	
Boiling point / boiling range	
Value	-50,9 °C
Source	supplier
Melting point/freezing point	
No data available	
Decomposition temperature	
No data available	
Flash point	
Not applicable	
Source	supplier
Ignition temperature	
Value	496 °C
Source	supplier
Explosive properties	
Risk of explosion when heated.	
Source	supplier
Flammability	
flammable	
Source	supplier
Lower explosion limit	
Value	11,3 % vol
Method	ASTM E 681

Trade name: R-454B

Current version : 2.0.0, issued: 26.06.2024

Replaced version: 1.0.0, issued: 14.12.2023

Region:
GER

Source	supplier		
Upper explosion limit			
Value	23,6	% vol	
Method	ASTM E 681		
Source	supplier		
Vapour pressure			
Value	15856	hPa	
Reference temperature	25	°C	
Source	supplier		
Relative vapour density			
Value	2,2		
Source	supplier		
Comments	Air = 1		
Evaporation rate			
Value	>	1	
Source	supplier		
Comments	CCl4 = 1		
Relative density			
Value	0,98		
Reference temperature	25	°C	
Source	supplier		
Density			
Value	0,98	g/cm ³	
Reference temperature	25	°C	
Source	supplier		
Comments	as liquid		
Solubility			
No data available			
Partition coefficient n-octanol/water (log value)			
No	Substance name	CAS no.	EC no.
1	difluoromethane	75-10-5	200-839-4
	log Pow	0,21	
	Reference temperature	25	°C
	with reference to	pH 6,1	
	Method	OECD 107	
	Source	ECHA	
2	2,3,3,3-tetrafluoroprop-1-ene	754-12-1	468-710-7
	log Pow	appr. 2	
	Reference temperature	25	°C
	with reference to	pH 7	
	Method	OECD 117	
	Source	ECHA	
Kinematic viscosity			
No data available			
Particle characteristics			
Not applicable			
Source	supplier		

9.2 Other information

Other information
No data available.

SECTION 10: Stability and reactivity**10.1 Reactivity**

This material is considered to be non-reactive under normal use conditions.

10.2 Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

10.3 Possibility of hazardous reactions

Reacts with strong oxidizing agents. Vapours can form a highly flammable mixture with air. Flammable gas.

10.4 Conditions to avoid

Heat, naked flames and other ignition sources. Temperatures > 50°C.

10.5 Incompatible materials

Avoid contamination (e.g. rust, dust, ash), risk of decomposition! Oxidizing agents; Acids; Bases; oxygen; Peroxides; Metal as powder

10.6 Hazardous decomposition products

None if stored, handled and transported properly. In case of fire: see section 5.

SECTION 11: Toxicological information**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute oral toxicity**

No data available

Acute dermal toxicity

No data available

Acute inhalational toxicity

No	Substance name	CAS no.	EC no.
1	difluoromethane	75-10-5	200-839-4
LC50	>	520000	ppmV
Duration of exposure		4	h
State of aggregation	Gas		
Species	rat		
Method	OECD 403		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
2	2,3,3,3-tetrafluoroprop-1-ene	754-12-1	468-710-7
LC50	>	405000	ppmV
Duration of exposure		4	h
State of aggregation	Gas		
Species	rat		
Method	OECD 403		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Skin corrosion/irritation

No data available

Serious eye damage/irritation

No data available

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No	Substance name	CAS no.	EC no.
1	difluoromethane	75-10-5	200-839-4
Type of examination	in vitro gene mutation study in bacteria		

Trade name: R-454B

Current version : 2.0.0, issued: 26.06.2024

Replaced version: 1.0.0, issued: 14.12.2023

Region:
GER

Species	Salmonella typhimurium / Escherichia coli
Method	OECD 471
Source	ECHA
Evaluation/classification	Based on available data, the classification criteria are not met.
Type of examination	In vitro Mammalian Chromosomal Aberration Test
Species	Human Lymphocyte
Method	OECD 473
Source	ECHA
Evaluation/classification	Based on available data, the classification criteria are not met.
Type of examination	In vivo mammalian somatic cell study: cytogenicity / erythrocyte micronucleus
Species	mouse
Method	OECD 474
Source	ECHA
Evaluation/classification	Based on available data, the classification criteria are not met.
2	2,3,3,3-tetrafluoroprop-1-ene 754-12-1 468-710-7
Type of examination	In vitro Mammalian Chromosomal Aberration Test
Species	Human Lymphocyte
Method	OECD 473
Source	ECHA
Evaluation/classification	Based on available data, the classification criteria are not met.
Route of exposure	inhalational
Type of examination	In vivo mammalian somatic cell study: cytogenicity / erythrocyte micronucleus
Species	rat
Method	OECD 474
Source	ECHA
Evaluation/classification	Based on available data, the classification criteria are not met.

Reproduction toxicity			
No	Substance name	CAS no.	EC no.
1	difluoromethane	75-10-5	200-839-4
Route of exposure		inhalational	
NOAEL		50000	ppm
Type of examination		Prenatal Developmental Toxicity Study	
Species		rabbit	
Method		OECD 414	
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are not met.	
2	2,3,3,3-tetrafluoroprop-1-ene	754-12-1	468-710-7
Route of exposure		inhalational	
NOAEC		> 50000	ppm
Type of examination		2 generation study	
Species		rat	
Method		OECD 416	
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are not met.	
Route of exposure		inhalational	
NOAEC		750	ppm
Type of examination		Prenatal Developmental Toxicity Study	
Species		rabbit	
Method		OECD 414	
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are not met.	

Carcinogenicity			
No	Substance name	CAS no.	EC no.
1	difluoromethane	75-10-5	200-839-4
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are not met.	

Trade name: R-454B

Current version : 2.0.0, issued: 26.06.2024

Replaced version: 1.0.0, issued: 14.12.2023

Region:
GER

STOT - single exposure			
No data available			
STOT - repeated exposure			
No	Substance name	CAS no.	EC no.
1	difluoromethane	75-10-5	200-839-4
Route of exposure		inhalational	
NOAEL		49100	ppm
Species	rat		
Method	OECD 413		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
2	2,3,3,3-tetrafluoroprop-1-ene	754-12-1	468-710-7
Route of exposure		inhalational	
NOAEC		50000	ppm
Species	rat		
Method	OECD 413		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
Aspiration hazard			
No data available			

11.2 Information on other hazards**Endocrine disrupting properties**

No data available.

Other information

No data available.

SECTION 12: Ecological information**12.1 Toxicity**

Toxicity to fish (acute)			
No	Substance name	CAS no.	EC no.
1	2,3,3,3-tetrafluoroprop-1-ene	754-12-1	468-710-7
LC50		>	197 mg/l
Duration of exposure			96 h
Species	Cyprinus carpio		
Method	OECD 203		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
Toxicity to fish (chronic)			
No data available			
Toxicity to Daphnia (acute)			
No	Substance name	CAS no.	EC no.
1	2,3,3,3-tetrafluoroprop-1-ene	754-12-1	468-710-7
EC50		>	100 mg/l
Duration of exposure			48 h
Species	Daphnia magna		
Method	OECD 202		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
Toxicity to Daphnia (chronic)			
No data available			
Toxicity to algae (acute)			

Trade name: R-454B

Current version : 2.0.0, issued: 26.06.2024

Replaced version: 1.0.0, issued: 14.12.2023

Region:
GER

No	Substance name	CAS no.	EC no.
1	2,3,3,3-tetrafluoroprop-1-ene	754-12-1	468-710-7
EC50	>	100	mg/l
Duration of exposure		72	h
Species	Pseudokirchneriella subcapitata		
Method	OECD 201		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Toxicity to algae (chronic)
No data available

Bacteria toxicity
No data available

12.2 Persistence and degradability

Biodegradability			
No	Substance name	CAS no.	EC no.
1	difluoromethane	75-10-5	200-839-4
Type	aerobic biodegradation		
Value		5	%
Duration		28	d
Method	OECD 301 D		
Source	ECHA		
Evaluation	not readily biodegradable		
2	2,3,3,3-tetrafluoroprop-1-ene	754-12-1	468-710-7
Type	aerobic biodegradation		
Value	<	5	%
Duration		28	d
Method	OECD 301 F		
Source	ECHA		
Evaluation	not readily biodegradable		

12.3 Bioaccumulative potential

Partition coefficient n-octanol/water (log value)			
No	Substance name	CAS no.	EC no.
1	difluoromethane	75-10-5	200-839-4
log Pow		0,21	
Reference temperature		25	°C
with reference to	pH 6,1		
Method	OECD 107		
Source	ECHA		
2	2,3,3,3-tetrafluoroprop-1-ene	754-12-1	468-710-7
log Pow	appr.	2	
Reference temperature		25	°C
with reference to	pH 7		
Method	OECD 117		
Source	ECHA		

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

Results of PBT and vPvB assessment	
PBT assessment	The product is not considered to be a PBT.
vPvB assessment	The product is not considered to be a vPvB.

12.6 Endocrine disrupting properties

No data available.

Trade name: R-454B

Current version : 2.0.0, issued: 26.06.2024

Replaced version: 1.0.0, issued: 14.12.2023

Region:
GER**12.7 Other adverse effects****Other adverse effects**

Contains fluorinated greenhouse gases.
Product: Global warming potential within 100 years: 465

12.8 Other information**Other information**

Do not discharge product unmonitored into the environment.

SECTION 13: Disposal considerations**13.1 Waste treatment methods****Product**

dispose of in accordance with local regulation.

Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement with the regional waste disposal company.

Packaging

Empty containers contain product residue and may be hazardous. Do not pressurize, cut, weld, braze, solder, drill or expose these containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death. Residues must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer.

SECTION 14: Transport information**14.1 UN number or ID number**

ADR/RID/ADN	UN3161
IMDG	UN3161
ICAO-TI / IATA	UN3161

14.2 UN proper shipping name

ADR/RID/ADN	LIQUEFIED GAS, FLAMMABLE, N.O.S.
Technical name	difluoromethane 2,3,3,3-tetrafluoroprop-1-ene
IMDG	LIQUEFIED GAS, FLAMMABLE, N.O.S.
Technical name	difluoromethane 2,3,3,3-tetrafluoroprop-1-ene
ICAO-TI / IATA	Liquefied gas, flammable, n.o.s.
Technical name	difluoromethane 2,3,3,3-tetrafluoroprop-1-ene

14.3 Transport hazard class(es)

ADR/RID/ADN - Class	2
Label	2.1 RID:(+13)
Classification code	2F
Tunnel restriction code	B/D
Hazard identification no.	23
IMDG - Class	2.1
Label	2.1
ICAO-TI / IATA - Class	2.1
Label	2.1

14.4 Packing group

Not classified as dangerous in the meaning of transport regulations.

14.5 Environmental hazards

EmS	F-D, S-U
-----	----------

Trade name: R-454B

Current version : 2.0.0, issued: 26.06.2024

Replaced version: 1.0.0, issued: 14.12.2023

Region:
GER**14.6 Special precautions for user**

To be transported always in closed, upright and safe containers. Make sure that persons handling these containers are aware of the rules of conduct in case of incident or spillage.

14.7 Maritime transport in bulk according to IMO instruments

Not relevant

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulations****Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)**

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

REACH candidate list of substances of very high concern (SVHC) for authorisation

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances subject to restriction as listed in Annex XVII of the REACH regulation (EC) 1907/2006.

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances

This product is not subject to Part 1 or 2 of Annex I.

Other regulations

REGULATION (EU) No 517/2014 on fluorinated greenhouse gases
Adhere to the national sanitary and occupational safety regulations when using this product.

National regulations**Water Hazard Class (Germany)**

Class

1

Source

Classification according to AwSV (Regulation on facilities for handling substances that are hazardous to water).

Other regulations

Take into account: TRGS 510 "Storage of hazardous substances in non-stationary containers"

15.2 Chemical safety assessment

Chemical safety assessments have been conducted for the substances in this mixture. For a mixture a chemical safety assessment according to (EC) 1907/2006 is not mandatory.

SECTION 16: Other information**Sources of key data used to compile the data sheet:**

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section.

Creation of the safety data sheet

UMCO GmbH

Trade name: R-454B

Current version : 2.0.0, issued: 26.06.2024

Replaced version: 1.0.0, issued: 14.12.2023

Region:
GER

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Alterations/supplements:

Alterations to the previous edition are marked in the left-hand margin.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH.

Prod-ID 772624